

556801

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
16 December 2004 (16.12.2004)

PCT

(10) International Publication Number
WO 2004/108576 A1

(51) International Patent Classification⁷: **B66B 5/28, 7/00**

(21) International Application Number:

PCT/US2003/017093

(22) International Filing Date: 30 May 2003 (30.05.2003)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): **OTIS ELEVATOR COMPANY** [US/US]; Ten Farm Springs Road, Farmington, CT 06032 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **McNAMARA, Brian T.** [IE/US]; 6298 North Viking Ridge Road, Bloomington, IN 47408 (US). **FEITL, Alfred R.** [US/US]; 2719 Glenn Ellen Drive, Bloomington, IN 47404 (US).

(74) Agent: **GASKEY, David J.**; Carlson, Gaskey & Olds, 400 W. Maple Rd., Ste. 350, Birmingham, MI 48009 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: **TIE-DOWN COMPENSATION FOR AN ELEVATOR SYSTEM**



(57) Abstract: An elevator system (20) includes a tie-down compensation arrangement (40). A tension member (42) extends between a cab (22) and counterweight (26) to provide a desired amount of tension on a load bearing rope or belt (30) that supports the cab and the counterweight. The tension member (42) in one example comprises a coated steel belt. At least one sheave (46) is supported on a base module (48) and remains stationary relative to a floor of a pit (52). A damper (50) is supported for movement with the counterweight (26) or the cab (22) to absorb energy that would otherwise tend to cause counterweight jump following a rapid descent and stop of the cab (22).

WO 2004/108576 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.